



3M Science.
Applied to Life.™

Unlock simplicity.
Hundreds of reattachments in a snap.

3M Industrial Adhesives and Tapes | 3M™ Dual Lock™ Reclosable Fasteners

Strong and simple to use.

3M™ Dual Lock™ Reclosable Fasteners

Not all design requirements are easily satisfied, but you can simplify your attachments. When you need a strong, reliable, yet removable closure or attachment, 3M™ Dual Lock™ Reclosable Fasteners are the easy alternative to traditional fastening methods such as screws, nuts or bolts.

- Strong, interlocking mushroom-shaped heads close with a snap to assure your design is securely fastened.
- The many adhesive options help to reduce concerns of material damage and deformation, fastener placement, contamination and corrosion, and the challenges of joining dissimilar materials.
- Works behind the scenes as an invisible fastener to create a snug fit and smooth lines for improved aesthetics and sleek appearances.
- Provides the application ease of tape and the durability of a traditional fastener.

Experience the simplicity

- Durable — up to 1,000 openings and closings before losing 50% of original tensile strength
- Helps reduce vibration
- Application and maintenance ease
- Pressure-sensitive adhesive easily forms a powerful bond
- Temperature, moisture and UV resistant
- Interlocking mushroom-shaped heads have **5X the tensile strength** of hook-and-loop products
- Low profile option available — approximately half the thickness of standard fastener



Reliable Performance

Strong, interlocking mushroom-shaped heads connect with an audible “snap”; Peel apart to open; Easily attach and detach multiple times

Customize for Your Application

Mix and match stem densities for the ideal closure strength; Choose from a variety of widths and adhesive options

Quick and Easy to Install

Adhesive sticks on contact to a variety of materials without special tools (no drilling, screwing, sewing); Non-adhesive product also available

Design Flexibility

Lightweight and low profile; Fastener is hidden beneath the surface and does not interfere with the integrity of the design; No holes or traditional fastener marks

Select the right 3M™ Dual Lock™ Reclosable Fastener for the job



Product	Stem Density (per sq/in)	Adhesive	Color	3M Liner	Engaged Thickness	Temperature Resistance
Specialty Vehicle						
SJ3550	250	White Acrylic	Black	Clear, 100µm Polyolefin	5.7mm	93°C
SJ3551	400					
SJ3552	170					
SJ3560	250	Clear Acrylic	Clear	Clear, 100µm Polyolefin	5.7mm	104°C
SJ4570	Low Profile	Low Surface Energy Acrylic	Clear	Brown, 165µm Polykraft	2.48mm	70°C

Substrates					Use	Applications			
Metals (Al, SS)	Glass	Plastics (Acrylic, PC, ABS)	Powder Coated Paints	Low Surface Energy (PP, PE)	Indoor/Outdoor	Interior Panels (Walls, doors, headliner, storage)	Accessory Attachment	Curtain Rails	Seats
■	●	■	▲	▲	Indoor/Outdoor	■	■	■	■
●	■	●	▲	▲	Indoor/Outdoor	●	●	●	●
●	●	●	■	■	Indoor	●	●	●	●



General Industrial						
SJ3550	250	White Acrylic	Black	Clear, 100µm Polyolefin	5.7mm	93°C
SJ3551	400					
SJ3552	170					
SJ3560	250	Clear Acrylic	Clear	Clear, 100µm Polyolefin	5.7mm	104°C
SJ4570	Low Profile	Low Surface Energy Acrylic	Clear	Brown, 165µm Polykraft	2.48mm	70°C

Metals (Al, SS)	Glass	Plastics (Acrylic, PC, ABS)	Powder Coated Paints	Low Surface Energy (PP, PE)	Indoor/Outdoor	Panel Assembly	Accessory Attachment	General Attachment	Floor Attachment
■	●	■	▲	▲	Indoor/Outdoor	■	■	■	■
●	■	●	▲	▲	Indoor/Outdoor	●	●	●	●
●	●	●	■	■	Indoor	●	●	●	●



POP, Display and Signage						
SJ3550	250	White Acrylic	Black	Clear, 100µm Polyolefin	5.7mm	93°C
SJ3551	400					
SJ3552	170					
SJ3560	250	Clear Acrylic	Clear	Clear, 100µm Polyolefin	5.7mm	104°C
SJ4570	Low Profile	Low Surface Energy Acrylic	Clear	Brown, 165µm Polykraft	2.48mm	70°C


Metals (Al, SS)	Glass	Plastics (Acrylic, PC, ABS)	Powder Coated Paints	Low Surface Energy (PP, PE)	Indoor/Outdoor	Trade Shows and Exhibits	Point of Purchase Displays	General Signage	Interior Design
●	●	●	▲	▲	Indoor/Outdoor	●	●	●	●
●	●	●	▲	▲	Indoor/Outdoor	●	●	●	●
■	■	■	■	■	Indoor	■	■	■	■

- Best Suggested Product
- Alternate Suggested Product
- ▲ Alternate Product — Must Use Primer

Meet the environmental and strength requirements for the application

Temperature Performance	
Best	SJ3560
Better	SJ3550
Good	SJ4570

Stem Density (per sq/in) Combinations	
Strongest	250:400
Stronger	250:250
Strong	170:250
Not Recommended	170:170 or 400:400



Type 400

Type 250

Type 170

Low Profile

Solve attachment challenges in an instant.

There are a thousand behind-the-scenes decisions that contribute to the success of your design. Every little feature — from how you choose to attach the graphics at a trade show or cushioning panels on a bus — matters for long term performance.

Choosing 3M™ Dual Lock™ Reclosable Fasteners can solve attachment challenges in an instant with the confidence that you've made the best decision for how your project will look when it's unveiled. Plus with the super strong bonds of 3M™ VHB™ Tape and powerful, interlocking mushroom-shaped heads, it also means you've chosen strength and easy to use reliable performance for the long run.

Ordering Information

Product	Stem Density (per sq/in)	Adhesive	3M Liner	Color	Description
SJ3550	250	Acrylic	Clear, 100µm Polyolefin	Black	3M™ Dual Lock™ Reclosable Fasteners, Black, Type 250
SJ3551	400	Acrylic		Black	3M™ Dual Lock™ Reclosable Fasteners, Black, Type 400
SJ3552	170	Acrylic		Black	3M™ Dual Lock™ Reclosable Fasteners, Black, Type 170
SJ3560	250	Clear Acrylic	Clear, 100µm Polyolefin	Clear	3M™ Dual Lock™ Reclosable Fasteners, Clear, Type 250
SJ4570	LP	Low Surface Energy Acrylic	Brown, 165µm Polykraft	Clear	3M™ Dual Lock™ Reclosable Fasteners, Low Profile, Clear

Additional 3M™ Dual Lock™ Reclosable Fasteners available.
For more information visit www.3M.co.uk/fasteners or call 0870 60 800 60



Secure plastic signs to window glass.



Attach cushioning panels in an ambulance or bus.



Anchor vehicle accessories to dashboard.



Attach access panels to industrial, electronic and electrical equipment.



Attach lift control panel to interior wall.



Fasten ceiling panels to interior for future access.



Industrial Adhesives and Tapes Division
3M United Kingdom plc
3M Centre, Cain Road
Bracknell, Berkshire RG12 8HT

Tel: 0870 60 800 60
www.3M.co.uk/fasteners

3M Ireland Limited
The Iveagh Building
The Park,
Carrickmines Dublin 18

Tel: 1800 320 500

Warranty, Limited Remedy and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M, "3M Science. Applied to Life.", Dual Lock and VHB are trademarks of 3M Company. All rights reserved.

3M is a trademark of the 3M company.
Please recycle. Printed in UK. © 2016, 3M. All rights reserved.
CJ1210A